




FUEL OIL DELIVERY | SPECIFICATION SHEET



FUELDEL250-XX 1" 250 PSI FUEL OIL DELIVE

APPLICATION

Designed to transfer fuel oils, diesel, or commercial gasolines. Compatible with bio-diesel fuels up to B20.

CONSTRUCTION

- **Tube** Nitrile RMA Class A
- **Cover** Nitrile RMA Class A / PVC Blend
- **Reinforcement** Four textile spirals

FEATURES

- Smooth cover resists dragging.
- Static wire included on all sizes.
- Designed for reel application.
- Temperature -40° to 212° F. Gasoline normally transferred below 120° F.
- 4:1 safety factor. Burst pressure to working pressure.



Part #	ID	OD	Max WP	Bend Radius	Weight	Coil Length
	inch	inch	psi	inch	lbs	feet
FUELDEL250-12	3/4	1.26	250	6.10	0.59	100/125/150/175
FUELDEL250-16	1	1.50	250	7.00	0.47	100/125/150/175
FUELDEL250-20	1-1/4	1.78	250	8.75	0.59	100/125/150/175
FUELDEL250-24	1-1/2	1.88	250	9.25	0.65	100/125/150/175
FUELDEL250-32	2	2.09	250	10.50	0.80	100/125/150/175

