




Clear/Green PVC Suction Specification Sheet



Part Number CS-XX



Part Number GS-XX

Clear/Green PVC Suction

Economical general service suction and discharge hose used for pumping water and light chemical solutions. PVC helix increases flexibility and abrasion resistance while the smooth interior provides maximum flow.

Tube PVC **Cover PVC**
Reinforcement Rigid poly helix
Safety Factor Minimum 3 to 1



-10° F to 130° F



ID	OD	Max WP	Suction	Bend Radius	Weight	Coil Length
inch	inch	psi	in./HG	inch	lbs./ft.	ft.
1	1.27	90	28	3	.27	100
1-1/4	1.56	90				
1-1/2	1.82	90		5	.47	
2	2.36	70		6	.66	
2-1/2	2.90	65		8	.92	
3	3.44	55		9	1.20	
4	4.52	50		13	1.87	
6	6.80	45		24	4.56	

TEST DOCUMENTATION

Clear

- ☐ 1"
- ☐ 1-1/4"
- ☐ 1-1/2"
- ☐ 2"
- ☐ 2-1/2"
- ☐ 3"
- ☐ 4"
- ☐ 6"

Green

- ☐ 1"
- ☐ 1-1/4"
- ☐ 1-1/2"
- ☐ 2"
- ☐ 2-1/2"
- ☐ 3"
- ☐ 4"
- ☐ 6"

APPROVAL PROCESS

JOB: _____ DATE: ____/____/____

MEETS DIMENSIONAL SPECIFICATIONS: ☐ YES ☐ NO

MEETS MATERIAL SPECIFICATIONS: ☐ YES ☐ NO

MEETS PRESSURE / TEMPERATURE SPECIFICATIONS: ☐ YES ☐ NO

NOTES: _____

ENGINEER NAME: _____

ENGINEER SIGNATURE: _____



**Midwest Hose
& Specialty, Inc.**



Find nearest location

Print setting must be on
best quality for scanning

Corporate Headquarters
3312 S. I-35 Service Road
Oklahoma City, OK 73129
405 - 670 - 6718

www.midwesthose.com