



Concrete Pumping Specification Sheet



Part Number MWHCRETE/T-XX



Part Number MWHCRETE/W-XX

Concrete Pumping

Designed to handle plaster, grout, and concrete at the critical flex areas of a concrete boom truck and high pump concrete boom.

Tube SBR/EPDM

Cover SBR/EPDM

Reinforcement System textile or high intensity steel wire

Safety Factor Minimum 2 to 1 (per CPMA standards)



-40° F to 180° F



Hose	ID inch	OD inch	Max WP psi	Bend Radius inch	Weight lbs/ft	Coil Length feet
Textile	1	1.69	800	10	0.7	50
	2	2.68	1233	20	1.6	50
	3	3.82	1233	30	2.5	50
	4	4.96	1233	40	3.2	100
	5	6.30	1233	50	4.3	100
Wire	1-1/2	2.16	1275	9.84	1.7	50
	2	2.75	1275	10.82	2.1	100
	2-1/2	3.46	1275	11.80	3.1	100
	3	3.86	1275	13.78	3.7	100
	4	5.02	1275	15.74	5.7	100
	5	6.00	1275	19.67	6.5	100

TEST DOCUMENTATION

Concrete Pumping Textile

- ☐ 1"
- ☐ 2"
- ☐ 3"
- ☐ 4"
- ☐ 5"

Concrete Pumping Wire

- ☐ 1-1/2"
- ☐ 2"
- ☐ 2-1/2"
- ☐ 3"
- ☐ 4"
- ☐ 5"

APPROVAL PROCESS

JOB: _____ DATE: ____/____/____

MEETS DIMENSIONAL SPECIFICATIONS: ☐ YES ☐ NO

MEETS MATERIAL SPECIFICATIONS: ☐ YES ☐ NO

MEETS PRESSURE / TEMPERATURE SPECIFICATIONS: ☐ YES ☐ NO

NOTES: _____

ENGINEER NAME: _____

ENGINEER SIGNATURE: _____



**Midwest Hose
& Specialty, Inc.**



Find nearest location

Print setting must be on
best quality for scanning

Corporate Headquarters
3312 S. I-35 Service Road
Oklahoma City, OK 73129
405 - 670 - 6718

www.midwesthose.com