



Hot Oiler Hydraulic Hose

Specification Sheet



Tube Synthetic Rubber

Cover Synthetic Rubber

Reinforcement Two high tensile steel wire braids

Hot Oiler	ID		OD	Max WP	Min BP	Bend Radius	Weight	Fitting Series	Coil Length
	inch	Tolerance	Tolerance	psi	psi	inch	lbs./ft.		
MWHHO-24	1-1/2	1.516 +/- .031	2.142 +/- .059	2,250	6,900	19.7	1.59	4WB	150

Approvals
MSHA cover

Maximum Abrasion Resistance (ISO 6945): 0.2 grams

TEST DOCUMENTATION



-40° F to 275° F
300° F intermittent

Hot Oiler

☐ 1-1/2"

APPROVAL PROCESS

JOB: _____ DATE: ____/____/____

MEETS DIMENSIONAL SPECIFICATIONS: ☐ YES ☐ NO

MEETS MATERIAL SPECIFICATIONS: ☐ YES ☐ NO

MEETS PRESSURE / TEMPERATURE SPECIFICATIONS: ☐ YES ☐ NO

NOTES: _____

ENGINEER NAME: _____

ENGINEER SIGNATURE: _____



**Midwest Hose
& Specialty, Inc.**



Find nearest location

Print setting must be on
best quality for scanning

Corporate Headquarters
3312 S. I-35 Service Road
Oklahoma City, OK 73129
405 - 670 - 6718

www.midwesthose.com