

N Liquid Mud 500 PSI Specification Sheet

> LIQUIDMUD500-64 500 PSI W.P. -40° to 180° F -40° to 82° C LIQUID MUD & FUEL DELIVERY DISCHARGE USE ONLY

Part Number LIQUIDMUD500-XX

Liquid Mud 500 PSI

Mud discharge hose designed for petroleum waste, drilling mud, diesel, and water. The standard to transfer liquid mud at high pressures from the mud pump.

Tube Nitrile (NBR) Cover Neoplane (CR) Reinforcement Synthetic textile Safety Factor Minimum 3 to 1



0&G W	ID ID	DD inch	Aax WP psi	Weight Ibs/ft	Coil Length feet
	2	2.87		1.67	
	3	3.86	500	2.84	200
	4	4.92	500	4.13	200
	6	7.18		5.50	
		TEST D	OCUMENTATION		

Liquid Mud 500 PSI

- □ 2″
- □ 3″
- 4″
- 6″

APPROVAL PROCESS

(JOB: DATE:/
	MEETS DIMENSIONAL SPECIFICATIONS: YES NO
	MEETS MATERIAL SPECIFICATIONS: YES NO
	MEETS PRESSURE / TEMPERATURE SPECIFICATIONS: YES NO
	NOTES:
	ENGINEER NAME:

ENGINEER SIGNATURE: .

Midwest Hose & Specialty, Inc.



Print setting must be on best quality for scanning

Corporate Headquarters 3312 S. I-35 Service Road Oklahoma City, OK 73129 405 - 670 - 6718 www.midwesthose.com