



Liquid Propane Gas 350 PSI

Specification Sheet



LPG-08 1/2" ID LIQUID PROPANE GAS UL UL 21

Designed to transfer liquid propane gas or butane. Can also transfer natural gas in open, well vented areas as 1 PSI max. UL21 LP Gas/Natural Gas approved

NOT for compressed natural gas.

Tube Nitrile

Cover Synthetic Rubber pin pricked





Reinforcement 1 or 2 textile braids

Safety Factor Minimum 4 to 1



-40° F to 140° F

LP Gas should never be above 100° F

 ID	 OD	 Max WP	 Weight	Reel Quantity
inch	inch	psi	lbs/ft	feet
1/4	.58	350	.12	500
3/8	.72		.17	
1/2	.91		.24	
3/4	1.23		.41	
1	1.5		.52	100 coil

TEST DOCUMENTATION



Liquid Propane Gas 350 PSI

- ☐ 1/4"
- ☐ 3/8"
- ☐ 1/2"
- ☐ 3/4"
- ☐ 1"

APPROVAL PROCESS

JOB: _____ DATE: ____/____/____

MEETS DIMENSIONAL SPECIFICATIONS: ☐ YES ☐ NO

MEETS MATERIAL SPECIFICATIONS: ☐ YES ☐ NO

MEETS PRESSURE / TEMPERATURE SPECIFICATIONS: ☐ YES ☐ NO

NOTES: _____

ENGINEER NAME: _____

ENGINEER SIGNATURE: _____



**Midwest Hose
& Specialty, Inc.**



Find nearest location

Print setting must be on
best quality for scanning

Corporate Headquarters
3312 S. I-35 Service Road
Oklahoma City, OK 73129
405 - 670 - 6718

www.midwesthose.com