

MWHR14SC PTFE Hose Specification Sheet

more flexible



Tube Teflon/PTFE spiral convoluted Cover Stainless steel braid

MWHR14SC		Braid ID	Braid OD	(Å) Max WP	Min BP	Bend Radius	Weight	Fitting
	inch	Tolerance (in.)	Tolerance (in.)	psi	psi	inch	lbs./ft.	Series
MWHR14SC-08	1/2	0.5"+/031"	0.82"+/031"	1,500	6,000	3.0	24.9	
MWHR14SC-12	3/4	0.75" +/031"	1.07" +/031"	1,200	4,800	3.5	32.3	
MWHR14SC-16	1	1.00"+/031"	1.34"+/031"	1,050	4,200	4.0	43.7	SCC
MWHR14SC-20	1-1/4	1.25" +/031"	1.57" +/031"	650	2,600	4.5	53.8	300
MWHR14SC-24	1-1/2	1.50"+/031"	1.81" +/031"	580	2,320	4.5	63.8	
MWHR14SC-32	2	2.0" +/031"	2.32" +/031"	500	2,000	5.5	89.4	

TEST DOCUMENTATION



-65° F to 450° F all teflon hoses

MWHR14SC PTFE Hose

- □ 1/2"
- □ 3/4"
- □ 1"
- □ 1-1/4"
- □ 1-1/2"
- □ 2″

APPROVAL PROCESS

JOB: DATE:/
MEETS DIMENSIONAL SPECIFICATIONS: YES NO
MEETS MATERIAL SPECIFICATIONS: YES NO
MEETS PRESSURE / TEMPERATURE SPECIFICATIONS: YES NO
NOTES:
ENGINEER NAME:
ENGINEER SIGNATURE:





best quality for scanning

Corporate Headquarters 3312 S. I-35 Service Road Oklahoma City, OK 73129 405 - 670 - 6718

www.midwesthose.com