











Noncollapsible Hose

Specification Sheet



Tube Nylon **Cover** Nylon

Reinforcement 316 Stainless steel interlocking carcass, minimum 5,000 psi differential pressure

Noncollapsible Hose								Normal Roll Length
	ID inch	OD inch	Max WP psi	Min BP psi	Bend Radius inch	Weight lbs./ft.	Fitting Series	
Approvals API 17E GP 65-06-03 GP 65-05-06	NCR5K-08	1/2	1.085	5,000	20,000	18	NCL	Continuous lengths over 10,000 feet
	NCR7.5K-12	3/4	1.455			18		
	NCR5K-16	1	1.740	7,500	30,000	20		
	NCR7.5K-08	1/2	1.185			18		

Capable of working in 10,000 feet of water.

TEST DOCUMENTATION



Noncollapsible NCR5K

- ☐ 1/2"
☐ 1"

Noncollapsible NCR7.5K

- ☐ 3/4"
☐ 1/2"

APPROVAL PROCESS

JOB: _____ DATE: ____/____/____

MEETS DIMENSIONAL SPECIFICATIONS: ☐ YES ☐ NO

MEETS MATERIAL SPECIFICATIONS: ☐ YES ☐ NO

MEETS PRESSURE / TEMPERATURE SPECIFICATIONS: ☐ YES ☐ NO

NOTES: _____

ENGINEER NAME: _____

ENGINEER SIGNATURE: _____



**Midwest Hose
& Specialty, Inc.**



Find nearest location

Print setting must be on
best quality for scanning

Corporate Headquarters
3312 S. I-35 Service Road
Oklahoma City, OK 73129
405 - 670 - 6718

www.midwesthose.com