



Oilfield Vacuum Corrugated 150 PSI

Specification Sheet



Part Number MWHOVC150-XX

Oilfield Vacuum Corrugated 150 PSI

Designed for oilfield waste pit recovery service. Ideal for handling crude oil, salt and freshwater, tank bottoms, and drilling mud up to 35% aromatics. Tube is designed to handle diluted solutions of hydrochloric acids and diesel fuels. Corrugated construction makes this hose more flexible.

Tube Nitrile RMA Type C **Cover** EPDM

Reinforcement Multiple textile plies, dual helix wire

Safety Factor Minimum 3 to 1



W

ID	OD	Max WP	Suction	Bend Radius	Weight	Coil Length
inch	inch	psi	in./HG	inch	lbs/ft	feet
1-1/2	1.89	150	30 Full Vacuum	5.9	0.79	100
2	2.48			9.1	1.30	
3	3.46			13.0	1.94	
4	4.57			17.1	3.04	
6	6.73			25.4	5.92	
8	8.82			42.1	8.77	65

TEST DOCUMENTATION



Oilfield Vacuum Corrugated 150 PSI

- ☐ 1-1/2"
- ☐ 2"
- ☐ 3"
- ☐ 4"
- ☐ 6"
- ☐ 8"

APPROVAL PROCESS

JOB: _____ DATE: ____/____/____

MEETS DIMENSIONAL SPECIFICATIONS: ☐ YES ☐ NO

MEETS MATERIAL SPECIFICATIONS: ☐ YES ☐ NO

MEETS PRESSURE / TEMPERATURE SPECIFICATIONS: ☐ YES ☐ NO

NOTES: _____

QC MANAGER NAME: MARK KOLDOFF

SIGNATURE: _____



**Midwest Hose
& Specialty, Inc.**



Find nearest location

Print setting must be on
best quality for scanning

Corporate Headquarters
3312 S. I-35 Service Road
Oklahoma City, OK 73129
405 - 670 - 6718

www.midwesthose.com