

# **Polyethylene Tubing FDA**

## **Specification Sheet**



### Polyethylene Tubing FDA

Linear low density polythylene food grade tubing for standard industrial applications such as the transfer of air and liquids, water lines, water softener lines, pneumatic logic control lines, and vending equipment.

Excellent resistance to solvents and stress cracking.



Safety Factor 3 to 1
Colors Natural off white (NA),
Black (BK), Yellow (YW), Orange (OR), Blue (B),
Red (R), Green (G), or FDA colors upon request.
Fittings Push-Connect, Self-Align, Mini Barb,
and Compression with 2030 inserts.

_	$\neg$
_ H	





Hoses	ID	OD	Wall Thickness	(A) Max WP	Weight
	inch	inch	inch	psi	lbs./100ft.
PE-04NA-500	.125	0.25	.0625	350	1.24
PE-44NA-500	.170	0.25	.040	150	1.2
PE-06NA-500	.250	0.375	.0625	150	3.0
PE-08NA-500	.375	0.5	.0625	125	3.4
PE-10NA-500	.500	0.625	.0625	100	5.0
PE-12NA-100	.625	0.75	.0625	100	5.5
PE-04MMNA-500	.106	4mm	.025	180	0.6
PE-06MMNA-500	4mm	6mm	1mm	150	1.1
PE-08MMNA-500	.236	8mm	.038	150	1.5
PE-10MMNA-500	8mm	10mm	1mm	125	2.1
PE-12MMNA-500	9mm	12mm	1.5mm	100	2.5

#### Polyethylene Tubing FDA

#### **APPROVAL PROCESS**

JOB: DATE:/
MEETS DIMENSIONAL SPECIFICATIONS:YESNO
MEETS MATERIAL SPECIFICATIONS: YES NO
MEETS PRESSURE / TEMPERATURE SPECIFICATIONS:YESNO
NOTES:
ENGINEER NAME:
ENGINEER SIGNATURE:





best quality for scanning

Corporate Headquarters 3312 S. I-35 Service Road Oklahoma City, OK 73129 405 - 670 - 6718 www.midwesthose.com