




Sandblast Specification Sheet



SANDBL150-12 3/4" ID SANDBLAST HOSE 150 PSI W.P.

Part Number SANDBL150-XX

Sandblast

Designed for sand, steel, shot, or other sharp abrasives to handle cleaning, cutting, or finishing stone, glass, or metal surfaces.

Static conductive tube prevents the build up of electrical charges.

Tube SBR/Natural rubber blend

Cover SBR/EPDM blend pin pricked

Reinforcement Synthetic textile

Safety Factor Minimum 4 to 1



-40° F to 180° F

A

MH

ID	OD	Max WP	Bend Radius	Weight	Coil Length
inch	inch	psi	inch	lbs/ft	feet
3/4	1.50	150	8	.57	100
1	1.88		12	.94	
1-1/4	2.13		14	1.18	
1-1/2	2.38		18	1.35	
2	2.78		20	1.74	

TEST DOCUMENTATION



Nozzle Blast Guide

Sandblast

- ☐ 3/4"
- ☐ 1"
- ☐ 1-1/4"
- ☐ 1-1/2"
- ☐ 2"

APPROVAL PROCESS

JOB: _____ DATE: ____/____/____

MEETS DIMENSIONAL SPECIFICATIONS: ☐ YES ☐ NO

MEETS MATERIAL SPECIFICATIONS: ☐ YES ☐ NO

MEETS PRESSURE / TEMPERATURE SPECIFICATIONS: ☐ YES ☐ NO

NOTES: _____

ENGINEER NAME: _____

ENGINEER SIGNATURE: _____



**Midwest Hose
& Specialty, Inc.**



Find nearest location

Print setting must be on
best quality for scanning

Corporate Headquarters
3312 S. I-35 Service Road
Oklahoma City, OK 73129
405 - 670 - 6718

www.midwesthose.com