




Tank Truck 300 PSI

Specification Sheet



Part Number MWHTT300-XX



Part Number MWHTTC300-XX

Tank Truck 300 PSI

Designed to handle diesel, ethanol, gasoline, oil, and petroleum based products that has up to 50% aromatics.

Corrugated construction gives the hose greater flexibility.

Tube Nitrile (NBR) **Cover** Neoprene (CR)

Reinforcement Multiple textile plies, dual helix wire

Safety Factor Minimum 3 to 1



W

Item	ID inch	OD inch	Max WP psi	Suction in./HG	Bend Radius inch	Weight lbs/ft	Coil Length feet
Smooth Cover	2	2.56	300	30 Full Vacuum	9.1	1.40	100/200
	3	3.62			13.2	2.36	
	4	4.70			17.3	3.45	
Corrugated Cover More Flexible	6	6.89			20.0	9.52	100
	8	9.06			30.0	10.20	65
	10	11.22			50.0	15.0	40

TEST DOCUMENTATION



Tank Truck Smooth 300 PSI

- ☐ 2"
- ☐ 3"
- ☐ 4"

Tank Truck Corrugated 300 PSI

- ☐ 6"
- ☐ 8"
- ☐ 10"

APPROVAL PROCESS

JOB: _____ DATE: ____/____/____

MEETS DIMENSIONAL SPECIFICATIONS: ☐ YES ☐ NO

MEETS MATERIAL SPECIFICATIONS: ☐ YES ☐ NO

MEETS PRESSURE / TEMPERATURE SPECIFICATIONS: ☐ YES ☐ NO

NOTES: _____

ENGINEER NAME: _____

ENGINEER SIGNATURE: _____



**Midwest Hose
& Specialty, Inc.**



Find nearest location

Print setting must be on
best quality for scanning

Corporate Headquarters
3312 S. I-35 Service Road
Oklahoma City, OK 73129
405 - 670 - 6718

www.midwesthose.com