



Tank Truck Corrugated 150 PSI

Specification Sheet



Part Number MWHTTC150-XX



Part Number MWHTTCRED150-XX

Tank Truck Corrugated 150 PSI

Designed to handle diesel, ethanol, gasoline, oil, and petroleum based products that has up to 50% aromatics.

Corrugated construction gives the hose greater flexibility.

Tube Nitrile (NBR) **Cover** Neoprene (CR)

Reinforcement Multiple textile plies, dual helix wire

Safety Factor Minimum 3 to 1



W

ID	OD	Max WP	Suction	Bend Radius	Weight	Coil Length
inch	inch	psi	in./HG	inch	lbs/ft	feet
2	2.48	150	30 Full Vacuum	4.0	1.18	100/200
3	3.50			6.0	1.99	100/200
4	4.56			9.0	2.66	100/200
6	6.75			8.0	4.17	100
8	8.81			20.0	6.02	65
10	11.02			40.0	13.92	40

TEST DOCUMENTATION

Tank Truck Corrugated 150 PSI

- ☐ 2"
- ☐ 3"
- ☐ 4"
- ☐ 6"
- ☐ 8"
- ☐ 10"

APPROVAL PROCESS

JOB: _____ DATE: ____/____/____

MEETS DIMENSIONAL SPECIFICATIONS: ☐ YES ☐ NO

MEETS MATERIAL SPECIFICATIONS: ☐ YES ☐ NO

MEETS PRESSURE / TEMPERATURE SPECIFICATIONS: ☐ YES ☐ NO

NOTES: _____

ENGINEER NAME: _____

ENGINEER SIGNATURE: _____



**Midwest Hose
& Specialty, Inc.**



Find nearest location

Print setting must be on
best quality for scanning

Corporate Headquarters
3312 S. I-35 Service Road
Oklahoma City, OK 73129
405 - 670 - 6718

www.midwesthose.com