



Tank Truck Corrugated 500 PSI

Specification Sheet



Part Number MWHTT500-XX

Tank Truck Corrugated 500 PSI

Designed to handle diesel, ethanol, gasoline, oil, and petroleum based products that has up to 50% aromatics.

Corrugated construction gives the hose greater flexibility.

Tube Nitrile (NBR) **Cover** Neoprene (CR)

Reinforcement

Safety Factor Minimum 3 to 1



ID	OD	Max WP	Suction	Bend Radius	Weight	Coil Length
inch	inch	psi	in./HG	inch	lbs/ft	feet
2	2.67	500	30	9.3	1.71	100/200
3	3.78		Full	13.6	2.94	
4	5.04		Vacuum	18.1	5.06	

TEST DOCUMENTATION

Tank Truck Corrugated 500 PSI

- ☐ 2"
- ☐ 3"
- ☐ 4"

APPROVAL PROCESS

JOB: _____ DATE: ____/____/____

MEETS DIMENSIONAL SPECIFICATIONS: ☐ YES ☐ NO

MEETS MATERIAL SPECIFICATIONS: ☐ YES ☐ NO

MEETS PRESSURE / TEMPERATURE SPECIFICATIONS: ☐ YES ☐ NO

NOTES: _____

ENGINEER NAME: _____

ENGINEER SIGNATURE: _____



**Midwest Hose
& Specialty, Inc.**



Find nearest location

Print setting must be on
best quality for scanning

Corporate Headquarters
3312 S. I-35 Service Road
Oklahoma City, OK 73129
405 - 670 - 6718

www.midwesthose.com