




Yellow Wire Braid Air

Specification Sheet



Part Number MWHYWX00-XX

Yellow Wire Braid Air

Designed for air-operated construction equipment, can handle oil mist from compressors. The standard for heavy duty rock drilling.

Tube Nitrile / SBR blend

Cover Neoprene / SBR blend

Reinforcement 2 wire braids

Safety Factor Minimum 3 to 1



ID	OD	Max WP	Suction	Bend Radius	Weight	Coil Length
inch	inch	psi	in./HG	inch	lbs/ft	feet
3/4	1.28	800	25	6	0.41	100
1	1.55			8	0.80	
1-1/4	1.80	600	15	10	1.02	
1-1/2	2.21			12	1.43	
2	2.66			14	1.93	
2-1/2	3.16			30	3.28	
3	3.72	500	10	36	4.10	
4	5.00			48	5.32	

TEST DOCUMENTATION

Yellow Wire Braid Air

- ☐ 3/4"
- ☐ 1"
- ☐ 1-1/4"
- ☐ 1-1/2"
- ☐ 2"
- ☐ 2-1/2"
- ☐ 3"
- ☐ 4"

APPROVAL PROCESS

JOB: _____ DATE: ____/____/____

MEETS DIMENSIONAL SPECIFICATIONS: ☐ YES ☐ NO

MEETS MATERIAL SPECIFICATIONS: ☐ YES ☐ NO

MEETS PRESSURE / TEMPERATURE SPECIFICATIONS: ☐ YES ☐ NO

NOTES: _____

ENGINEER NAME: _____

ENGINEER SIGNATURE: _____



Midwest Hose
& Specialty, Inc.



Find nearest location

Print setting must be on
best quality for scanning

Corporate Headquarters
3312 S. I-35 Service Road
Oklahoma City, OK 73129
405 - 670 - 6718

www.midwesthose.com