


Water Discharge Industrial Hoses Specification Sheet



Part Number MWHWD2PLY-XX



Part Number MWHWD4PLY-XX

Water Discharge

Designed for water discharge in construction, heavy duty equipment rental, and mines and quarries.

Soft-wall hose construction provides similar performance to a layflat hose but a higher working pressure and more abrasion resistance.

Tube SBR Cover SBR Reinforcement Synthetic textile Safety Factor 3 to 1



W

Hose	₽	OD	(A) Max WP	W Weight	Coil Length
	inch	inch	psi	lbs/ft	feet
2 Ply	1-1/2	1.78	150	0.44	- 100
	2	2.28		0.62	
	2-1/2	2.78		0.75	
	3	3.28		0.95	
	4	4.31		1.25	
	6	6.31		2.68	
	8	8.72	100	3.77	
	10	10.42	80	5.00	
	1-1/2	1.89	250	0.55	100
4 Ply	2	2.39		1.00	
	2-1/2	2.89		1.33	
	3	3.39		1.58	
	4	4.43	200	2.15	
	6	6.43		3.25	
	8	8.47	150	4.50	
	10	10.53		5.50	
	12	12.53		8.00	50

TEST DOCUMENTATION

Water Discharge 2 Ply	Water Discharge 4 Ply		
☐ 1-1/2″	☐ 1-1/2 <i>"</i>		
□ 2″	□ 2″		
□ 2-1/2″	□ 2-1/2″		
□ 3″	□ 3″		
□ 4″	□ 4"		
□ 6″	□ 6″		
□ 8″	□ 8″		
□ 10″	□ 10"		
	□ 12″		

APPROVAL PROCESS
DATE:/
TS DIMENSIONAL SPECIFICATIONS: YES NO
TS MATERIAL SPECIFICATIONS: ☐ YES ☐ NO
S PRESSURE / TEMPERATURE SPECIFICATIONS: YES NO
ES:
NEER NAME:
NEER SIGNATURE:



