



# Push-On 300 PSI

## Specification Sheet



**Part Number** MWHMPUSH300-XX

### Push-On 300 PSI

Designed for use with push-on fittings for air tools, petroleum products, gasoline, mild chemicals or water. No clamps or special tools required. Hose reinforcement laid at the most effective angle for maximum strength and coupling holding ability. **Non-conductive.**

**Tube** Nitrile RMA Class A

**Cover** Neoprene, MSHA approved

**Reinforcement** Braided textile

**Safety Factor** Minimum 3 to 1



-40° F to 190° F



ID	OD	Max WP	Bend Radius	Weight	Reel Quantity
inch	inch	psi	inch	lbs/ft	feet
1/4	.54	300	3	.09	700
3/8	.69		3	.14	
1/2	.81		5	.17	
5/8	.93		6	.20	
3/4	1.07		7	.26	
1	1.19		8	.30	500

TEST DOCUMENTATION

### Push-On 300 PSI

- 1/4"
- 3/8"
- 1/2"
- 5/8"
- 3/4"
- 1"

### APPROVAL PROCESS

JOB: \_\_\_\_\_ DATE: \_\_\_\_/\_\_\_\_/\_\_\_\_

MEETS DIMENSIONAL SPECIFICATIONS:  YES  NO

MEETS MATERIAL SPECIFICATIONS:  YES  NO

MEETS PRESSURE / TEMPERATURE SPECIFICATIONS:  YES  NO

NOTES: \_\_\_\_\_

ENGINEER NAME: \_\_\_\_\_

ENGINEER SIGNATURE: \_\_\_\_\_



**Midwest Hose & Specialty, Inc.**



Find nearest location

Print setting must be on best quality for scanning

Corporate Headquarters  
3312 S. I-35 Service Road  
Oklahoma City, OK 73129  
405 - 670 - 6718

[www.midwesthose.com](http://www.midwesthose.com)