



Clear/Green PVC Suction Specification Sheet



Part Number CS-XX



Part Number GS-XX

Clear/Green PVC Suction

Economical general service suction and discharge hose used for pumping water and light chemical solutions. PVC helix increases flexibility and abrasion resistance while the smooth interior provides maximum flow.

Tube PVC **Cover PVC**
Reinforcement Rigid poly helix
Safety Factor Minimum 3 to 1



-10° F to 130° F



 ID	 OD	 Max WP	 Suction	 Bend Radius	 Weight	 Coil Length
inch	inch	psi	in./HG	inch	lbs./ft.	ft.
1	1.27	90	28	3	.27	100
1-1/4	1.56	90				
1-1/2	1.82	90		5	.47	
2	2.36	70		6	.66	
2-1/2	2.90	65		8	.92	
3	3.44	55		9	1.20	
4	4.52	50		13	1.87	
6	6.80	45		24	4.56	

TEST DOCUMENTATION 

Popular Assemblies Camlocks

2" GS32-CG-A32CAMC-A32CAME-20FT

3" GS48-CG-A48CAMC-A48CAME-20FT

4" GS64-CG-A64CAMC-A64CAME-20FT

Popular Assemblies Pin Lugs

2" GS32-CG-A32PLM-A32PLF-20FT

3" GS48-CG-A48PLM-A48PLF-20FT

4" GS64-CG-A64PLM-A64PLF-20FT

Popular Assemblies MP x Female Cam with Strainer

2" GS32-CS-32KC-A32CAMC-20FT+STR-RH200

3" GS48-CS-48KC-A48CAMC-20FT+STR-RH300

4" GS64-CS-64KC-A64CAMC-20FT+STR-RH400

6" GS96-CS-96KC-A96CAMC-20FT+STR-RH600

Popular Assemblies Plated MP x Female Pin Lug with Strainer

2" GS32-CS-P32KC-32PLF-20FT+STR-RH200

3" GS48-CS-P48KC-48PLF-20FT+STR-RH300

4" GS64-CS-P64KC-64PLF-20FT+STR-RH400

6" GS96-CS-P96KC-96PLF-20FT+STR-RH600



**Midwest Hose
& Specialty, Inc.**



Find nearest location

Print setting must be on
best quality for scanning

Corporate Headquarters
3312 S. I-35 Service Road
Oklahoma City, OK 73129
405 - 670 - 6718

www.midwesthose.com