




# FUEL OIL DELIVERY | SPECIFICATION SHEET



**FUELDEL250-XX 1" 250 PSI FUEL OIL DELIVE**

## APPLICATION

Designed to transfer fuel oils, diesel, or commercial gasolines. Compatible with bio-diesel fuels up to B20.








## CONSTRUCTION

- **Tube** Nitrile RMA Class A
- **Cover** Nitrile RMA Class A / PVC Blend
- **Reinforcement** Four textile spirals

## FEATURES

- Smooth cover resists dragging.
- Static wire included on all sizes.
- Designed for reel application.
- Temperature -40° to 212° F. Gasoline normally transferred below 120° F.
- 4:1 safety factor. Burst pressure to working pressure.



						
Part #	ID	OD	Max WP	Bend Radius	Weight	Coil Length
	inch	inch	psi	inch	lbs	feet
FUELDEL250-12	3/4	1.26	250	6.10	0.59	100/125/150/175
FUELDEL250-16	1	1.50	250	7.00	0.47	100/125/150/175
FUELDEL250-20	1-1/4	1.78	250	8.75	0.59	100/125/150/175
FUELDEL250-24	1-1/2	1.88	250	9.25	0.65	100/125/150/175



**MIDWEST HOSE & SPECIALTY**

Corporate Headquarters | 3312 S. I-35 Service Road  
Oklahoma City, OK 73129 | 405 - 670 - 6718 | [www.midwesthose.com](http://www.midwesthose.com)