



LAYFLAT DISCHARGE | SPECIFICATION SHEET



APPLICATION

General purpose hoses for open end discharge. Non-absorbing, mildew proof, and rolls up flat for easy storage and handling. Common in construction, agriculture, irrigation, marine, and rental applications. PVC hoses resistant to oils, grease.

CONSTRUCTION

- **Tube** and **cover** are extruded simultaneously to achieve maximum bonding.
- **Reinforcement** Polyester yarn

FEATURES

- **Temperature** -5° to 170° F
- **Safety Factor** 3 to 1

Part Number	Class	ID	Wall Thickness	Max WP	Burst	Length
		inch	inch	psi	psi	feet
BD-100, GD-100	Standard	1	0.052	110	195	300
BD-125, GD-125	Standard	1-1/4	0.056	80	195	300
BD-150, GD-150	Standard	1-1/2	0.059	80	195	300
BD-200, GD-200	Standard	2	0.059	80	195	300
BD-250, GD-250	Standard	2-1/2	0.059	65	195	300
BD-300, GD-300	Standard	3	0.063	80	180	300
BD-400, GD-400	Standard	4	0.067	70	165	300
BD-600, GD-600	Standard	6	0.075	60	135	300
BD-800, GD-800	Standard	8	0.087	35	105	300
REDHD-150, YELHD-150	Heavy Duty	1-1/2	0.079	150	450	300
REDHD-200, YELHD-200	Heavy Duty	2	0.087	150	450	300
REDHD-300, YELHD-300	Heavy Duty	3	0.095	150	400	300
REDHD-400, YELHD-400	Heavy Duty	4	0.102	125	400	300
REDHD-600, YELHD-600	Heavy Duty	6	0.119	115	280	300
REDHD-800, YELHD-800	Heavy Duty	8	0.134	70	190	300

