

Tank Truck 300 PSI **Specification Sheet**



Part Number MWHTT300-XX



Part Number MWHTTC300-XX

Tank Truck 300 PSI

Designed to handle diesel, ethanol, gasoline, oil, and petroleum based products that has up to 50% aromatics.

Corrugated construction gives the hose greater flexibility.

Tube Nitrile (NBR) **Cover** Neoprene (CR) Reinforcement Multiple textile plies, dual helix wire

Safety Factor Minimum 3 to 1





| Item | <u>D</u> | . G | Max WP | Suction | Bend Radius | | |
|--------------------------------------|----------|------------|--------|----------------------|----------------|--------|---------|
| | inch | inch | psi | in./HG | inch | lbs/ft | feet |
| Smooth Cover | 2 | 2.56 | 300 | 30 Full Vacuum | 9.1 | 1.40 | 100/200 |
| | 3 | 3.62 | | | 13.2 | 2.36 | |
| | 4 | 4.70 | | | 17.3 | 3.45 | |
| Corrugated Cover More Flexible | 6 | 6.89 | | | 20.0 | 9.52 | 100 |
| | 8 | 9.06 | | | 30.0 | 10.20 | 65 |
| | 10 | 11.22 | | | 50.0 | 15.0 | 40 |
| | | | | TECT DOCUMENTATION | | | |

Tank Truck Smooth 300 PSI

- □ 2"
- □ 3″
- □ 4″

Tank Truck Corrugated 300 PSI

- □ 6"
- □ 8"
- □ 10″

APPROVAL PROCESS

| JOB: | DATE:/ |
|----------------------------|----------------------------|
| MEETS DIMENSIONAL SPECIFIC | |
| MEETS MATERIAL SPECIFICATI | IONS: YES NO |
| MEETS PRESSURE / TEMPERAT | URE SPECIFICATIONS: YES NO |
| NOTES: | |
| | |
| ENGINEER NAME: | |
| ENGINEER SIGNATURE: | |





best quality for scanning