










Choke & Kill with Abrasion Resistant Cover Specification Sheet



Tube Nitrile

Reinforcement 6 or 8 steel wire spiral layers

Cover Neoprene/PVC (PVC improves ozone and ageing resistance)

CKARC							
		ID	OD	Max WP	Test Pressure	Bend Radius at WP	Weight
		inch	inch	psi	psi	inch	lbs./ft.
Designed for cementing service or acidizing service on a drilling rig. Used as a flexible connection (instead of pipe) to connect the cementing pump manifold and cementing head. higher abrasion resistance	CKARC-24-10K	1-1/2	2.32	10,000	15,000	19.69	3.423
	CKARC-32-10K	2	2.83			23.62	4.471



Max Length 150 feet

Min Burst Requirement 24,000 psi

CKARC

☐ 1-1/2"

☐ 2"

APPROVAL PROCESS

JOB: _____ DATE: ____/____/____

MEETS DIMENSIONAL SPECIFICATIONS: ☐ YES ☐ NO

MEETS MATERIAL SPECIFICATIONS: ☐ YES ☐ NO

MEETS PRESSURE / TEMPERATURE SPECIFICATIONS: ☐ YES ☐ NO

NOTES: _____

ENGINEER NAME: _____

ENGINEER SIGNATURE: _____



**Midwest Hose
& Specialty, Inc.**



Find nearest location

Print setting must be on
best quality for scanning

Corporate Headquarters
3312 S. I-35 Service Road
Oklahoma City, OK 73129
405 - 670 - 6718

www.midwesthose.com