

F1SC/TC HYDRAULIC HOSE

SPECIFICATION SHEET



Part #	ID	OD/Tolerance	Max WP	Min BP	Bend Radius	Weight
F1SC/TC-XX	INCH	INCH	PSI	PSI	INCH	LBS/FT
F1SC/TC-04	1/4	0.492 +/- 0.016	3265	13060	2.0	0.13
F1SC/TC-06	3/8	0.626 +/- 0.016	2610	10440	2.6	0.19
F1SC/TC-08	1/2	0.760 +/- 0.020	2325	9300	3.5	0.24
F1SC/TC-10	5/8	0.906 +/- 0.020	1885	7540	4.0	0.33
F1SC/TC-12	3/4	1.051 +/- 0.020	1525	6100	4.7	0.42
F1SC/TC-16	1	1.374 +/- 0.020	1275	5100	6.0	0.61

Application: Designed for delivering water and petroleum-based hydraulic fluids

Construction:


Tube: Oil resistant synthetic rubber

Cover: Abrasion, ozone, oil, and weather resistant synthetic rubber

Reinforcement: One wire braid of high tensile steel

Temperature: -40°F to 212°F

Safety Factor: 4:1



MIDWEST HOSE & SPECIALTY

Corporate Headquarters | 3312 S. I-35 Service Road

OKC, OK 73129 | 405-670-6718 | www.midwesthose.com