

# F4K/TC HYDRAULIC HOSE

## SPECIFICATION SHEET



Part #	ID	OD/Tolerance	Max WP	Min BP	Bend Radius	Weight
F4K/TC-XX	INCH	INCH	PSI	PSI	INCH	LBS/FT
F4K/TC-04	1/4	0.531 +/- 0.016	4000	16000	1.8	0.19
F4K/TC-06	3/8	0.685 +/- 0.016	4000	16000	2.6	0.28
F4K/TC-08	1/2	0.811 +/- 0.016	4000	16000	3.2	0.34
F4K/TC-10	5/8	0.972 +/- 0.020	4000	16000	3.5	0.50
F4K/TC-12	3/4	1.091 +/- 0.020	4000	16000	4.7	0.58
F4K/TC-16	1	1.409 +/- 0.020	4000	16000	6.0	0.86
F4K/TC-20	1-1/4	1.791 +/- 0.020	4000	16000	8.3	1.77
F4K/TC-24	1-1/2	2.106 +/- 0.020	4000	16000	9.8	2.25
F4K/TC-32	2	2.681 +/- 0.020	4000	16000	13.8	3.21

**Application:** Designed for petroleum base hydraulic fluids and lubricating oils

**Construction:**


**Tube:** Oil resistant synthetic rubber

**Cover:** Abrasion, ozone, oil, and weather resistant synthetic rubber

**Reinforcement:** Two or four wire braids of high tensile steel

**Temperature:** -40°F to 212°F

**Safety Factor:** 4:1



## MIDWEST HOSE & SPECIALTY

Corporate Headquarters | 3312 S. I-35 Service Road

OKC, OK 73129 | 405-670-6718 | [www.midwesthose.com](http://www.midwesthose.com)