



F4K/TC HYDRAULIC HOSE

SPECIFICATION SHEET



Part #	ID	OD/Tolerance	Max WP	Min BP	Bend Radius	Weight
F4K/TC-XX	INCH	INCH	PSI	PSI	INCH	LBS
F4K/TC-04	1/4	0.531 +/- 0.016	4000	16000	1.772	0.639
F4K/TC-06	3/8	0.685 +/- 0.016	4000	16000	2.559	0.926
F4K/TC-08	1/2	0.811 +/- 0.016	4000	16000	3.150	1.124
F4K/TC-10	5/8	0.972 +/- 0.020	4000	16000	3.543	1.631
F4K/TC-12	3/4	1.091 +/- 0.020	4000	16000	4.724	1.896
F4K/TC-16	1	1.409 +/- 0.020	4000	16000	5.906	2.822
F4K/TC-20	1-1/4	1.791 +/- 0.020	4000	16000	8.268	5.798
F4K/TC-24	1-1/2	2.106 +/- 0.020	4000	16000	9.843	7.385
F4K/TC-32	2	2.681 +/- 0.020	4000	16000	13.780	10.538

Application: Designed for petroleum base hydraulic fluids and lubricating oils

Construction:

Tube: Oil resistant synthetic rubber

Cover: Abrasion, ozone, oil, and weather resistant synthetic rubber

Reinforcement: Two or four wire braids of high tensile steel

Temperature: -40°F to 212°F

Safety Factor: 4:1



MIDWEST HOSE & SPECIALTY

Corporate Headquarters | 3312 S. I-35 Service Road

OKC, OK 73129 | 405-670-6718 | www.midwesthose.com