



F5K/TC HYDRAULIC HOSE

SPECIFICATION SHEET



Part #	ID	OD/Tolerance	Max WP	Min BP	Bend Radius	Weight
F5K/TC-XX	INCH	INCH	PSI	PSI	INCH	LBS
F5K/TC-04	1/4	0.531 +/- 0.016	5000	20000	1.969	0.639
F5K/TC-06	3/8	0.673 +/- 0.016	5000	20000	2.559	0.904
F5K/TC-08	1/2	0.799 +/- 0.020	5000	20000	3.150	1.213
F5K/TC-12	3/4	1.268 +/- 0.020	5000	20000	4.724	2.976
F5K/TC-16	1	1.524 +/- 0.020	5000	20000	5.906	4.541
F5K/TC-20	1-1/4	1.791 +/- 0.024	5000	20000	8.268	5.798
F5K/TC-24	1-1/2	2.256 +/- 0.024	5000	20000	9.843	11.574
F5K/TC-32	2	2.831 +/- 0.024	5000	20000	24.803	15.454

Application: Designed for petroleum base hydraulic fluids and lubricating oils

Construction:

Tube: Oil resistant synthetic rubber

Cover: Abrasion, ozone, oil, and weather resistant synthetic rubber

Reinforcement: Two, four, or six wire braids/spirals of high tensile steel

Temperature: -40°F to 248°F

Safety Factor: 4:1



MIDWEST HOSE & SPECIALTY

Corporate Headquarters | 3312 S. I-35 Service Road

OKC, OK 73129 | 405-670-6718 | www.midwesthose.com