

F6K/TC HYDRAULIC HOSE

SPECIFICATION SHEET



Part #	ID	OD/Tolerance	Max WP	Min BP	Bend Radius	Weight
F6K/TC-XX	INCH	INCH	PSI	PSI	INCH	LBS/FT
F6K/TC-04	1/4	0.516 +/- 0.016	6000	24000	2.0	0.19
F6K/TC-06	3/8	0.815 +/- 0.016	6000	24000	2.6	0.50
F6K/TC-08	1/2	0.906 +/- 0.020	6000	24000	3.5	0.56
F6K/TC-10	5/8	1.043 +/- 0.020	6000	24000	4.0	0.66
F6K/TC-12	3/4	1.268 +/- 0.020	6000	24000	5.5	1.04
F6K/TC-16	1	1.543 +/- 0.020	6000	24000	6.0	1.44
F6K/TC-20	1-1/4	1.945 +/- 0.020	6000	24000	8.3	2.79
F6K/TC-24	1-1/2	2.256 +/- 0.020	6000	24000	9.8	3.53
F6K/TC-32	2	2.831 +/- 0.024	6000	24000	24.8	4.71

Application: Designed for petroleum base hydraulic fluids and lubricating oils

Construction:


Tube: Oil resistant synthetic rubber

Cover: Abrasion, ozone, oil, and weather resistant synthetic rubber

Reinforcement: Two, four, or six wire braids/spirals of high tensile steel

Temperature: -40°F to 248°F

Safety Factor: 4:1



MIDWEST HOSE & SPECIALTY

Corporate Headquarters | 3312 S. I-35 Service Road

OKC, OK 73129 | 405-670-6718 | www.midwesthose.com