

# High Pressure Water Jetting Specification Sheet



#### Part Number WATERJ1500-XX

# **High Pressure Water**

### **Jetting**

Designed to transfer water in inland water ways and offshore high pressure water jetting service. Meets all USCG requirements.

8" or assemblies more than 60 feet require special delivery

Tube Nitrile (NBR)
Cover Neoprene (CR)
Reinforcement Multiple wire braids
Safety Factor Minimum 3 to 1



-20° F to 200° F

A	





<u> </u>	OD OD	Max WP	Bend Radius	w Weight	Coil Length
inch	inch	psi	inch	lbs/ft	feet
4	5.19		16	7.8	
6	7.50	1500	24	14.1	100
8	9.75		32	22.4	

TEST DOCUMENTATION

## **High Pressure Water Jetting**

□ 4"

□ 6″

□ 8″

#### APPROVAL PROCESS

/	JOB:	DATE:	_/		1
	MEETS DIMENSIONAL SPECIFICATIONS: Y	ES NO			
	MEETS MATERIAL SPECIFICATIONS: YES	NO			
	MEETS PRESSURE / TEMPERATURE SPECIFICA	TIONS:	YES N	10	
	NOTES:				
	ENGINEER NAME:				
	ENGINEER SIGNATURE:				/





best quality for scanning

Corporate Headquarters 3312 S. I-35 Service Road Oklahoma City, OK 73129 405 - 670 - 6718 www.midwesthose.com