



# Hot Oiler Hydraulic Hose

## Specification Sheet



**Tube** Synthetic Rubber

**Cover** Synthetic Rubber

**Reinforcement** Two high tensile steel wire braids

Hot Oiler	ID		OD	Max WP	Min BP	Bend Radius	Weight	Fitting Series	Coil Length
	inch	Tolerance	Tolerance	psi	psi	inch	lbs./ft.		
MWHHO-24	1-1/2	1.516 +/- .031	2.142 +/- .059	2,250	6,900	19.7	1.59	4WB	150

**Approvals**  
MSHA cover

Maximum Abrasion Resistance (ISO 6945): 0.2 grams

**TEST DOCUMENTATION**



-40° F to 275° F  
300° F intermittent

### Hot Oiler

☐ 1-1/2"

### APPROVAL PROCESS

JOB: \_\_\_\_\_ DATE: \_\_\_\_/\_\_\_\_/\_\_\_\_

MEETS DIMENSIONAL SPECIFICATIONS: ☐ YES ☐ NO

MEETS MATERIAL SPECIFICATIONS: ☐ YES ☐ NO

MEETS PRESSURE / TEMPERATURE SPECIFICATIONS: ☐ YES ☐ NO

NOTES: \_\_\_\_\_

ENGINEER NAME: \_\_\_\_\_

ENGINEER SIGNATURE: \_\_\_\_\_



**Midwest Hose  
& Specialty, Inc.**



Find nearest location

Print setting must be on  
best quality for scanning

Corporate Headquarters  
3312 S. I-35 Service Road  
Oklahoma City, OK 73129  
405 - 670 - 6718

[www.midwesthose.com](http://www.midwesthose.com)