

Single Jacket Mill Hose Specification Sheet



Single Jacket Mill Hose

Designed for open end discharge applications. Uses include connections to fire hydrants, dust control water trucks, water spraying, and water discharge. Immune to mildew.

Tube Single ply synthetic rubber **Cover** Polyester Length up to 100 feet W

	IO	((w
ltem	ID	SP psi	Bowl Size	Weight Per 50' Uncpld.
MILL-24	1.5"	250	1-3/4"	10 lbs.
MILL-32	2"		2-1/4"	11.5 lbs.
MILL-40	2.5"		2-11/16"	17 lbs.
MILL-48	3"		3-1/4	21 lbs.
MILL-64	4"		4-3/8"	40 lbs.

Rated pressure: 250 PSI at ambient temperature 70°F (21°C) Working pressure: 125 PSI at ambient temperature 70°F (21°C)

Single Mill Hose 24 □ 1.5"

Single Mill Hose 32

□ 2′

Single Mill Hose 40

□ 2.5″

Single Mill Hose 48

□ 3″

Single Mill Hose 64

□ 4'

APPROVAL PROCESS

	7.11.11.0 17.12.1 11.0 02.23				
/	JOB:	DATE:/			
	MEETS DIMENSIONAL SPECIFICATIONS: Y	ES NO			
	MEETS MATERIAL SPECIFICATIONS: YES	NO			
	MEETS PRESSURE / TEMPERATURE SPECIFICA	ATIONS: YES NO			
	NOTES:				
	ENGINEER NAME:				
	ENGINEER SIGNATURE:				





best quality for scanning