

Tank Truck Corrugated 150 PSI Specification Sheet

MWHTTC150-64 4" ID 150 PSI W.P. -40" to 180" F -40" to 82" C TANK TRUCK CORRUGATED SUCTION & DISCHARGE

Part Number MWHTTC150-XX

MW⁺⁻ MWHTTCRED150-64 4" ID ¹⁵⁰ PSI W.P. -40° to 180° F -40° to 82° C TANK TRUCK CORRUGATED UNIT

Part Number MWHTTCRED150-XX

Tank Truck Corrugated 150 PSI

Designed to handle diesel, ethanol, gasoline, oil, and petroleum based products that has up to 50% aromatics.

Corrugated construction gives the hose greater flexibility.

Tube Nitrile (NBR) Cover Neoprene (CR) Reinforcement Multiple textile plies, dual helix wire Safety Factor Minimum 3 to 1

0&G W	<u>∎</u>		Aax WP)(Suction		w Weight	
	inch	inch	psi	in./HG	inch	lbs/ft	feet
	2	2.48	150	30 Full Vacuum	4.0	1.18	100/200
	3	3.50			6.0	1.99	100/200
	4	4.56			9.0	2.66	100/200
	6	6.75			8.0	4.17	100
	8	8.81			20.0	6.02	65
	10	11.02			40.0	13.92	40
				TEST DOCUM	NENTATION		

Tank Truck Corrugated 1	50 PSI
-------------------------	--------

- 2″
- □ 3″
- □ 4″
- 6″
- 8″
- □ 10″

APPROVA	L PROCESS
JOB:	DATE:/
MEETS DIMENSIONAL SPECIFICATIO	DNS: YES NO
MEETS MATERIAL SPECIFICATIONS:	
MEETS PRESSURE / TEMPERATURE S	SPECIFICATIONS: YES NO
NOTES:	
ENGINEER NAME:	

ENGINEER SIGNATURE:

Midwest Hose & Specialty, Inc.

Find nearest location

Print setting must be on best quality for scanning

Corporate Headquarters 3312 S. I-35 Service Road Oklahoma City, OK 73129 405 - 670 - 6718 www.midwesthose.com