

Tank Truck Corrugated 500 PSI Specification Sheet



Part Number MWHTT500-XX

Tank Truck Corrugated 500 PSI

Designed to handle diesel, ethanol, gasoline, oil, and petroleum based products that has up to 50% aromatics.

Corrugated construction gives the hose greater flexibility.

Tube Nitrile (NBR) Cover Neoprene (CR)
Reinforcement
Safety Factor Minimum 3 to 1





ID ID	© 60	(Å) Max WP)(Suction	Bend Radius	w Weight	Coil Length
inch	inch	psi	in./HG	inch	lbs/ft	feet
2	2.67		30	9.3	1.71	
3	3.78	500	Full	13.6	2.94	100/200
4	5.04		Vacuum	18.1	5.06	
			TECT DOCUM	IENTATION III		

Tank Truck Corrugated 500 PSI

□ 2″

□ 3"

□ 4″

APPROVAL PROCESS

JOB:	DATE:/
MEETS DIMENSIONAL SPECIFIC	ATIONS: YES NO
MEETS MATERIAL SPECIFICATIO	NS: YES NO
MEETS PRESSURE / TEMPERATU	RE SPECIFICATIONS: YES NO
NOTES:	
ENGINEER NAME:	
ENGINEER SIGNATURE:	



