



Tank Truck Corrugated Low Temp 150 PSI Specification Sheet



Part Number MWHTTCLT150-64

Tank Truck Corrugated Low Temp 150 PSI

Designed to handle diesel, ethanol, gasoline, oil, and petroleum based products that has up to 50% aromatics.

Corrugated construction with low temperature features make this our most flexible tank truck hose.

Tube Nitrile (NBR) **Cover** Neoprene (CR)

Reinforcement Multiple textile plies, dual helix wire

Safety Factor Minimum 3 to 1



-65° F to 180° F

LT

O&G

W

ID	OD	Max WP	Suction	Bend Radius	Weight	Coil Length
inch	inch	psi	in./HG	inch	lbs/ft	feet
2	2.48	150	30	4.0	1.25	100
3	3.50		Full	6.0	2.02	
4	4.57		Vacuum	9.0	2.94	

TEST DOCUMENTATION

Tank Truck Corrugated Low Temp 150 PSI

- ☐ 2"
☐ 3"
☐ 4"

APPROVAL PROCESS

JOB: _____ DATE: ____/____/____

MEETS DIMENSIONAL SPECIFICATIONS: ☐ YES ☐ NO

MEETS MATERIAL SPECIFICATIONS: ☐ YES ☐ NO

MEETS PRESSURE / TEMPERATURE SPECIFICATIONS: ☐ YES ☐ NO

NOTES: _____

ENGINEER NAME: _____

ENGINEER SIGNATURE: _____



**Midwest Hose
& Specialty, Inc.**



Find nearest location

Print setting must be on
best quality for scanning

Corporate Headquarters
3312 S. I-35 Service Road
Oklahoma City, OK 73129
405 - 670 - 6718

www.midwesthose.com